

IW-RS118-03

=Motherboard=

Brand	Model	CPU Socket	Form Factor
Asrockrack	EP2C622D16NM	Socket-3647	EEB 12" x 13"
Supermicro	H11SSL-NC	Socket-4094 SP3	ATX

=CPU=

Brand	Model	Form Factor	TDP
Intel®	Xeon® Gold 6150 CPU 2.7GHz	Purley	165W
AMD	EPYC PS7451BDVHCAF 2.9GHz	EPYC(SP3)	180W

=Hard Disk Drive=

Brand	Model	Interface	Form Factor	Capacity	RPM Class
Seagate	ST200FM0053	SAS 12G SSD	2.5"	200GB	-

=RAID Card=

Brand	Model	Ports	Data Rates	RAID Level
LSI	9361-8i	Internal x 8	SATA/SAS 12G	0,1,5,6,10,50,60
LSI	9460-16i	Internal x 16(NVMe x4)	SATA/SAS 12G	0,1,5,6,10,50,60

=Heatsink=

Brand	Model	Form Factor	CPU Socket	TDP
Dynatron	B4	Purley Narrow	Socket-3647	205W
Dynatron	A25(passive)	EPYC	socket-4094(SP3r2)	180W

Note:

- * The listed components had been tested by In Win lab according to In Win's verification standard.
- * To avoid failure and errors, please also reference components vendors' user manual.
- * The actual performance is affected by host's hardware specification, software, file system, and other conditions.