

IW-RS104-02M

=Motherboard=

Brand	Model	CPU Socket	Form Factor
Intel	S2600ST	Socket-3647	EEB 12" x 13"
Asrockrack	EP2C612D16C-4L	Socket-2011	EEB12" x 13"
Asrockrack	EP2C612D16-2L2T	Socket-2011	EEB12" x 13"
Asrockrack	C236M-WS	Socket-1151	ATX-UP
Supermicro	X10DRL-I	Socket-2011	ATX-DP
Supermicro	X10SRL-F	Socket-2011	ATX-UP
ASUS	Z11PR-D16	Socket-3647	EEB 12" x 13"

=CPU=

Brand	Model	Form Factor	TDP
Intel®	Xeon® scalable 8160	Purley	150W
Intel®	Xeon® scalable 6150	Purley	165W
Intel®	Xeon® E5-2637	Socket-2011 V3	135W

=Hard Disk Drive=

Brand	Model	Interface	Form Factor	Capacity	RPM Class
WD	WD5000BPKX	SATA 3	2.5"	500GB	7200
Seagate	ST336754SS	SAS 3G	3.5"	36GB	15000
Seagate	ST8000NM0075	SAS 12G	3.5"	8TB	7200
Toshiba	PX02SMF020-SSD	SAS 12G	2.5"	200GB	SSD
HGST	HUC156030CSS200	SAS 12G	2.5"	300GB	15000

=Power Supply=

Brand	Model	Output Watt	80+ Level	Form Factor
AcBel	EP1A5501B	550W	Gold	Single
PowerOne	SPSINWN-04GS313	750W	Platinum	Redundant

=RAID Card=

Brand	Model	Ports	Data Rates	RAID Level
LSI	9361-8i	Internal x 8	SATA/SAS 12G	0,1,5,6,10,50,60
LSI	9361-8i	Internal x 8	SATA/SAS 6G	0,1,5,6,10,50,60
LSI	9271-8i	Internal x 8	SATA/SAS 6G	0,1,5,6,10,50,60
Intel	C236 onboard SATA RAID	Internal x 8	SATA III	0,1,5,10

=Heatsink=

Brand	Model	Form Factor	CPU Socket	TDP
Dynatron	T318A	1U	Socket-2011	165W
Intel	AXXSTPHMKIT1U	1U/Square	Socket-3647	165W
Dynatron	B5	1U/Square	Socket-3647	165W
Dynatron	K129	1U	Socket-1151	105W



Note:

- * The listed components had been tested by In Win lab according to In Win's verification standard.
- * To avoid failure and errors, please also reference components vendors' user manual.
- * The actual performance is affected by host's hardware specification, software, file system, and other conditions.