

IW-RS212-02M

=Motherboard=

Brand	Model	CPU Socket	Form Factor
Asrockrack	EP2C612D16C-4L	Socket-2011	EEB12"x13"
Supermicro	X10DAC	Socket-2011	EEB12"x13"

=Hard Disk Drive=

Brand	Model	Interface	Form Factor	Capacity	RPM Class
Seagate	ST1500DL003	SATA 3	3.5"	1.5TB	7200
Seagate	ST3300657SS	SAS 6G	3.5"	300GB	15000
Seagate	ST336754SS	SAS 3G	3.5"	36GB	15000
Seagate	ST8000NM0075	SAS 12G	3.5"	8TB	7200

=Power Supply=

Brand	Model	Output Watt	80+ Level	Form Factor
Acbel	EP1A5501B	500W	Gold	Single
Acbel	R2IS7651A	650W	Gold	Redundant
Acbel	R1CA2551B	550W	Platinum	Redundant
Acbel	R1CA2801A	800W	Platinum	Redundant

=RAID Card=

Brand	Model	Ports	Data Rates	RAID Level
LSI	9260-8i	Internal x8	SATA/SAS 6G	0,1,5,6,10,50,60
Adaptec	ASR6805	Internal x8	SATA/SAS 6G	0,1,5,6,10,50,60

=Heatsink=

Brand	Model	Form Factor	CPU Socket	TDP
Dynatron	R14	Narrow	Socket2011	150W
Dynatron	R5	Square	Socket2011	165W

Note:

- * The listed components had been tested by In Win lab according to In Win's verification standard.
- * To avoid failure and errors, please also reference components vendors' user manual.
- * The actual performance is affected by host's hardware specification, software, file system, and other conditions.