

## IW-RS224-03

### =Motherboard=

Brand	Model	CPU Socket	Form Factor
Intel	S1200SPL	Socket-1151	uATX
Asrockrack	EP2C612D8-2T8R	Socket-2011	ATX
Asrockrack	EP2C612D8-8R	Socket-2011	ATX

### =Hard Disk Drive=

Brand	Model	Interface	Form Factor	Capacity	RPM Class
HGST	HUC156030CSS200	SAS 12G	2.5"	300GB	15000
HGST	HUSMH8010BSS201	SAS 12G	2.5"	100GB	SSD
Seagate	ST9146803SS	SAS 6G	2.5"	146GB	10000
Seagate	ST500LT02	SATA 3	2.5"	500GB	5400
Seagate	ST9250610NS	SATA 3	2.5"	250GB	7200
WD	WD5000BPKX-75HPJT0	SATA 3	2.5"	500GB	7200
Toshiba	PX02SMF020	SAS 12G	2.5"	200GB	SSD

### =RAID Card=

Brand	Model	Ports	Data Rates	RAID Level
LSI	9361-8i	Internal x 8	SATA/SAS 12G	0,1,5,6,10,50,60
LSI	9260-8i	Internal x 8	SATA/SAS 6G	0,1,5,6,10,50,60
LSI	3008 onboard HBA	Internal x 8	SATA/SAS 6G	0,1
ATTO	H1288 HBA 8e+8i	Int./Ext. x 8	SATA/SAS 12G	0,1

### =Heatsink=

Brand	Model	Form Factor	CPU Socket	TDP
Dynatron	R14	Narrow	Socket2011	150W
Dynatron	R5	Square	Socket2011	165W
Dynatron	K666	Square	Socket 1151	95W

#### Note:

- \* The listed components had been tested by In Win lab according to In Win's verification standard.
- \* To avoid failure and errors, please also reference components vendors' user manual.
- \* The actual performance is affected by host's hardware specification, software, file system, and other conditions.