

## IW-RS248-03

### =Motherboard=

Brand	Model	CPU Socket	Form Factor
ASROCKRACK	EP2C622D16NM	Socket-3647	EEB
Supermicro	H11SSL-NC	Socket-4094 SP3	ATX

### =CPU=

Brand	Model	Form Factor	TDP
Intel®	Xeon® Gold 6150 CPU 2.7GHz	Purley	165W
AMD	EPYC PS7451BDVHCAF 2.9GHz	Socket-4094(SP3r2)	180W

### =Hard Disk Drive=

Brand	Model	Interface	Form Factor	Capacity	RPM Class
Seagate	ST200FM0053	SAS SSD	2.5"	200GB	-
Intel®	SSD 730	SATA SSD	2.5"	450GB	-
Intel®	SSD DC P4501 SERIES 500GB	NVMe	2.5"	500GB	-
Seagate	ST500LT012	SATA	2.5"	500GB	5400 RPM
Toshiba	PX02SMF020	SAS 12GB SSD	2.5"	200GB	-
Seagate	ST9250610NS	SATA	2.5"	250GB	7200 RPM

### =RAID Card=

Brand	Model	Ports	Data Rates	RAID Level
LSI	9361-8i	Internal x 8	SATA/SAS 12G	0,1,5,6,10,50,60
LSI	9460-16i (16 port SAS/SATA)	Internal x 4 NVMe	SATA/SAS 12G	0,1,5,6,10,50,60

### =Heatsink=

Brand	Model	Form Factor	CPU Socket	TDP
Dynatron	B5	Purley Narrow	Socket-3647	205W
Dynatron	A26	EPYC	socket-4094(SP3r2)	180W

#### Note:

- \* The listed components had been tested by In Win lab according to In Win's verification standard.
- \* To avoid failure and errors, please also reference components vendors' user manual.
- \* The actual performance is affected by host's hardware specification, software, file system, and other conditions.