

## IW-RS104-07

### =Motherboard=

Brand	Model	CPU Socket	Form Factor
ASROCKRACK	EP2C622D16NM	Socket-3647	EEB
Intel	S2600ST	Socket-3647	EEB
Supermicro	H11SSL-NC	Socket-4094(SP3)	ATX

### =CPU=

Brand	Model	CPU Socket	Form Factor	TDP
Intel®	Xeon® Platinum 8160	Socket-3647	Purley	150W
AMD	EPYC PS7451BDVHCAF 2.9GHz	Socket-4094	EPYC (SP3)	180W

### =Hard Disk Drive=

Brand	Model	Interface	Form Factor	Capacity	RPM Class
WD	WD2005FBYZ	SATA	3.5"	2TB	7200 RPM
WD	WD3001FYYG	SAS	3.5"	3TB	7200 RPM
WD	WD4001FYYG	SAS	3.5"	4TB	7200 RPM
Intel®	SSD 730	SATA SSD	2.5"	450GB	-
Intel®	P750 800GB SSD	NVMe	2.5" 25W	800GB	-
Seagate	ST12000NM0038	SAS	3.5"	12TB	7200 RPM
Seagate	ST336754SS	SAS	3.5"	36GB	15000 RPM

### =PAID Card=

Brand	Model	Ports	Data Rates	RAID Level
LSI	9361-8i	Internal x 8	SATA/SAS 12G	0,1,5,6,10,50,60
LSI	9460-16i	Internal x 4 NVMe	SATA/SAS 12G	0,1,5,6,10,50,60

### =Heatsink=

Brand	Model	Form Factor	CPU Socket	TDP
Dynatron	B4	Purley Narrow	Socket-3647	205W
Dynatron	B4A	Purley Narrow	Socket-3647	205W
Dynatron	B6	Purley Square	Socket-3647	205W
Dynatron	A25	EPYC	Socket-4094(SP3r2)	180W

#### Note:

- \* The listed components had been tested by In Win lab according to In Win's verification standard.
- \* To avoid failure and errors, please also reference components vendors' user manual.
- \* The actual performance is affected by host's hardware specification, software, file system, and other conditions.