

## IW-PLG Tower

### =Motherboard=

Brand	Model	CPU Socket	Form Factor
ASROCKRACK	EP2C612 WS	Socket-2011	EEB (GPU x4)
ASUS	WS C621E SAGE	Socket-3647	EEB (GPUx4)
Gigabyte	MZ01-CEO	Socket-4094	ATX
Asrockrack	EPYCD8	Socket-4094	ATX

### =CPU=

Brand	Model	Form Factor	TDP
Intel	Xeon® Platinum 8160M	Socket-3647	150W
Intel	Xeon® E5-2637 V3	Socket-2011	130W
AMD	EPYC 7451	Socket-4094	180W

### =Hard Disk Drive=

Brand	Model	Interface	Form Factor	Capacity	RPM Class
WD	WD2005FBYZ	SATA	3.5"	2TB	7200rpm
WD	WD60EFRX-68L0BN1	SATA	3.5"	6TB	5400rpm

### =Power supply=

Brand	Model	Wattle	Form Factor	Note
Acbel	R1CA2202B	2000W	1+1	220V only GPUx4
Acbel	R1CA2162A	1600W	1+1	220V only GPUx4
Acbel	R1CA2122A	1200W	1+1	110V only GPUx2
Acbel	R1CA2801A	800W	1+1	110V only GPUx1

### =Heatsink=

Brand	Model	Form Factor	CPU Socket	TDP
Dynatron	R5	Square	Socket-2011	165W
Intel	AXXSTPHMKIT2U	Square	Socket-3647	165W
Dynatron	A26	2U Active	Socket-SP3(4096)	180W

#### Note:

- \* GPU Test sample use GTX 1080Ti 250W of ASUS
- \* The listed components had been tested by In Win lab according to In Win's verification standard.
- \* To avoid failure and errors, please also reference components vendors' user manual.
- \* The actual performance is affected by host's hardware specification, software, file system, and other conditions.